

NB340

Conventional Wall Mounted Chime



Listed

The **NB-340 Conventional Wall Mounted Chime** is a two-wire appliance that operates on a FACP (fire alarm control panel) or **SFM (Synchronized Function Module)** command to provide audible indication of alarm condition. When the notification appliance emits sound, it indicates the possibility of an emergency situation that requires your immediate attention. The chime has adjustable sound level, and has a chime tone adjustable from 750 to 1250 Hz. The appliances are not to be painted or the finish altered in any way.

Key Features

- Operates when the supply voltage is connected to the device
- The **NB-345 Conventional Mini-Horn** can be synchronized when Wizmart's **SFM Synchronized Function Module** (configured by its DIP selection switches) is used.
- 24 V DC operation
- Adjustable sound level
- Loud sounder output
- Low maintenance
- Easy installation

TECHNICAL SPECIFICATIONS

| | |
|---------------------------|---|
| OPERATING VOLTAGE | 16 ~ 33 V DC |
| REVERSE CURRENT | 40 µA |
| ALARM CURRENT @ 24V DC | 25 mA |
| SOUNDER OUTPUT | 30 ~ 65 dB @ 3 m Adjustable |
| SOUNDER FREQUENCY | 750 ~ 1250 Hz Adjustable |
| TERMINAL WIRING | 18AWG ~ 12AWG (0.82 mm ² ~3.31 mm ²) |
| OPERATING TEMPERATURE | 0 °C ~ +50 °C |
| OPERATING HUMIDITY | 10 % ~ 93 % RH, non-condensing at 38 °C |
| DIMENSIONS (w x h x d) | (133 x 130 x43) mm |
| INGRESS PROTECTION RATING | IP-22 |

ORDER CODE

| | |
|---------|--------------------------------|
| NB340-R | Conventional Mini-Horn - RED |
| NB340-W | Conventional Mini-Horn - WHITE |

